

NEW CONSTRUCTION • R-Values

| New Construction | R-Value Code | Types Of Insulation Options Offered By: Maritime Insulators | R-Value Pre-Inch | Thickness Required In Inches To Achieve Code |
|--|--------------|--|----------------------|--|
| Exterior Walls | R-24 | Closed Cell Spray Foam | R-6 | 5.5" |
| | | Fiberglass Batts | R-4.36 | 5.5" |
| | | Cellulose Density Packed | R-3.8 | 6.5" |
| Exterior Cement Walls | R-20 | Closed Cell | R-6 | 4" |
| | | Spray Foam Batts | R-3.64 | 5.5" |
| Attic Flat Roof Decks | R-50 | Closed Cell Spray Foam | R-6 | 8.5" |
| | | Cellulose Blown-in | R-3.35 | 15" |
| | | Fiberglass Blown-in | R-2.8 | 19" |
| | | Fiberglass Batts | R-3.64 | 13.75" |
| | | Closed Cell & Cellulose | CC R-6 Cell R-3.8 | 16" |
| Roof Slopes With Venting | R-28 | Closed Cell Spray Foam | R-6 | 6.7" |
| | | Cellulose Blown-in | R-3.35 | 10.35" |
| | | Fiberglass Blown-in | R-3.4 | 10.25" |
| | | Fiberglass Batts | R-3.64 | 9.75" |
| Hot Roof Slope Application: No Venting | R-31 | Closed Cell Spray Foam | R-6 | 6" |
| Floor Of Overhang Crawl Space Floor | R-31 | Closed Cell | R-6 | 6" |
| Under Slab | R-12 | Closed Cell | R-6 | 2" |
| Garage Ceiling With Living Space Above It | R-31 | Closed Cell | R-6 | 5.5" |
| | | Fiberglass Batt | R-3.64 | 8.5" |